

00AL Jib Reefing & Furling

SMALL BOAT HEADSAIL HANDLING

Unit 00AL is the perfect jib reefing and furling system for small cruising and racing boats under 26 ft (8 m). It combines most of the features of larger Harken® furling systems in a simpler unit.

These free-rolling systems make all the difference in headsail control, allowing cruisers to quickly furl and reef while maintaining optimal speed. Smoothly unfurl your headsail instead of hoisting a large genoa in light air. Now you can stay off the foredeck during a blow and rely on the furler for 'crew' when sailing shorthanded.



HEADSAIL HANDLING

EASY FURLING

This strong, lightweight furler features multiple rows of Torlon® ball bearings to minimize friction for smooth furling. The large inner spool diameter makes furling easier.

STANDS UP TO THE ELEMENTS

Deep-saturation Hardkote-anodized halyard swivel, line guard, torque tube and bearing races resist the corrosive effects of saltwater and sun and provide long-term wear.

RACE MODE

Aerodynamic foil's double grooves and stainless steel feeder allow fast hoists, douses and sail changes. Split drum and line guard come off easily to use with full-hoist sails.

INSTALLATION

00AL furling systems are designed for owner installation over existing turnbuckle after some initial rigging work is completed. The headstay will need to be cut, foil connectors slid on, then a swage or Norseman/Sta-Lok terminal installed. Turnbuckle is easy to adjust by simply raising the drum.



1112



909

Typical Boat Length 20' - 26' (6 - 8 m)

Wire Ø (1 x 19 SS)	Rod Ø	Clevis Pin Ø
1/8", 5/32", 3/16" (3, 4, 5 mm)	-4, 4.37 mm	1/4", 5/16", 3/8", 7/16" (6, 8, 9.5, 11 mm)
Headstay Length	Standard 9.60 m (31'6"); max 10.67 m (35')	
Part No.	Description	
1110	Furling system	
Clevis Pin Assembly Required - sold separately		
1106	1/4" (6 mm)	
1107	5/16" (8 mm)	
1108	3/8" (9.5 mm)	
1109	7/16" (11 mm)	
Optional Parts		
909	Extra 6" (152 mm) connector	
1112	Extra 3.5' (1.07 m) foil extrusion	
7404	Lead block kit: 3 x 7403/1 x 7402/1 x 7401/1 cleat	
884	Snap shackle for tack/head (each shackle)	
061	Stanchion mount base	
944	Halyard restrainer (use only when required)	