

T18™ Soft-Attach Blocks

This tough little soft-attach is lighter than a small standard metal shackle. It ties, splices, or lashes anywhere, including tight spaces. A perfect complement to the T2™ blocks on skiffs, dinghies, and beachcats.



Actual Size

USES

Control lines and take-ups on dinghies, skiffs, and beachcats; especially downhauls, outhauls, and other systems where very small blocks are required.

FEATURES

7.2 grams (.25 oz)—20% lighter weight and 10% smaller than comparably sized blocks.

MWL: 125 kg (275 lb)

Soft attachment allows block to articulate and align with the load; ties or splices to almost anything.

Line routes through the block head and sheave; reduces load on sideplates.

Max line size 5 mm (3/16 in).

MATERIALS

Fiber-reinforced, nylon-resin sideplates for strength. Integrated inner race and rivet are 316 stainless steel. High-wear composite sheave is impact-resistant.

Sheave spins on stainless steel balls in captive grooved race for an optimal strength-to-weight ratio in a very small package.

A length of 1.8 mm (1/16 in) line is included.

MAINTENANCE

The simple construction requires no lubrication. Blocks flush clean with fresh water.



T18™ blocks can be tied, spliced, or lashed to nearly anything.



Stainless steel balls in captive grooved race for low-friction rolling.

Blocks

| Part No. | Description | Sheave Ø | | Length | | Weight | | Max line Ø | | Maximum working load | | Breaking load | |
|----------|-------------|----------|----|--------|----|--------|-----|------------|----|----------------------|-----|---------------|-----|
| | | in | mm | in | mm | oz | g | in | mm | lb | kg | lb | kg |
| 2698 | Single | 23/32 | 18 | 1 1/8 | 28 | .25 | 7.2 | 3/16 | 5 | 275 | 125 | 992 | 450 |