

T2™ Soft-Attach Blocks



The all-composite T2™ is the first block with no metal shackles or rivets and is the lightest soft-attach block Harken has ever designed. Soft attachments provide a fair lead to reduce friction. The T2™ Loop requires no knots, splices, or tools to install, while the T2™ comes with a length of line that can be tied, spliced, or lashed to almost anything.



Slide the loop through the head and over the anchor post for a secure connection.

USES

Use for lightweight traveler controls, in mainsheet and vang systems, cascades, bridles, and more.

FEATURES

T2™ Loop

The loop slides easily through the block head and over the anchor post for a secure connection. No knots, splices, or tools required.

An SK 75 Dyneema® loop is included with each block. Replacement loops available on request.

Blocks come in 40 and 57 mm single sizes.

T2™

Tie, splice, or lash to almost anything.

Replacement Loops

Part No.	Ø		Length		Weight		Use with
	in	mm	in	mm	oz	g	
2154	1/8	3	5 1/8	130	.03	.9	2148
2155	1/8	3	5 7/8	150	.04	1	2151

Blocks

Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Maximum working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	lb	kg	lb	kg
T2™													
2146	Single	1 1/8	29	1 11/16	43	0.4	12	5/16	8	330	150	1000	454
2149	Single	1 9/16	40	2 1/4	57	0.9	25	3/8	10	485	220	1200	544
2152	Single	2 1/4	57	3 1/16	79	2	57	7/16	10	792	359	2380	1080
T2™ Loop													
2148	Single*	1 9/16	40	2 1/4	57	0.9	26	3/8	10	485	220	1200	544
2151	Single**	2 1/4	57	3 1/16	79	2	59	7/16	10	792	359	2380	1080

*Includes 2154 loop **Includes 2155 loop

A length of covered Spectra® line is included.

Blocks come in 29 mm, 40 mm, and 57 mm sizes.

MATERIALS

Fiber-reinforced high-strength nylon-resin sideplates have no metal fasteners for the lightest block in Harken history. Both models route the attachment line through the block head and sheave, reducing load on the sideplates and acting as a safety backup for your system.

Composite sheave spins on ball bearings with fitted races for low-friction rolling.

Soft attachments reduce weight and noise while allowing the block to articulate to align with the load.

MAINTENANCE

The simple construction requires no lubrication. Blocks flush clean with fresh water.



T2™ Loop Blocks come in 40 and 57 mm sizes.



This block offers the most flexibility. It can be tied, spliced, or lashed to nearly anything. Available in 29, 40, and 57 mm.